



GB

Taper with Radius End Burs

Solid Carbide

* 8mm shanks optional. To Order Optional Cuts 4, 3SP, 2, 5 - Specify Quantity, Tool No. & Optional Cut

ES

Limas rotativas cónicas a 8°-14° punta esférica

Metal duro

* Mango de 8 mm opcional. Para ordenar cortes opcionales 4, 3SP y 2, 5 : Especificque la cantidad, no. de herramienta y tipo de corte opcional.

FR

Fraises-limes de forme conique, à bout hémisphérique

Carbure monobloc

* Queue de 8 mm en option. Pour commander les coupes en option 4, 3SP, 2, 5 : indiquer la quantité, le N° d'outil et la coupe.

PT

Limas rotativas no formato de cone com topo arredondado

Metal duro
* Encabadouro/haste de 8mm opcional para pedidos de cortes opcionais 4, 3SP, 2, 5 - Especificar quantidade, N° de ferramenta e corte opcional.

IT

Lime rotative forma conica a 8°-14° con testa sferica

Metallo duro

* Disponibile anche con gambo diametro 8mm. Per ordinare tipi di tagliente speciale 4 / 3sp / 2 / 5, specificate: quantità, articolo e tipo di tagliente

DE

Frässtifte Rundkegelform

Vollhartmetall
* 8 mm Schaft auf Wunsch lieferbar
Um andere Verzahnungen zu bestellen: Bitte Tool No. und Verzahnungsart gemäß Seite 71 angeben.



Tool No.	ød ₁ mm	ød ₂ mm	l ₁ mm	l ₂ mm	α	EDP No.	EDP No.	EDP No.
SL-41M	3	3	38	9,5	8°	25403	25400	
SL-42M	3	3	38	12,7	8°	25428	25425	
SL-42ML2	3	3	50	12,7	8°	27953	27950	
SL-42ML3	3	3	75	12,7	8°	27978	27975	
SL-53M	5	3	38	12,7	14°	25453	25450	
SL-1M	6	6	50	16	14°	25178	25175	
SL-1ML6	6	6	166	16	14°	26753	26750	
SL-2M	8	6	69	22	14°	25203	25200	
SL-3M	9,5	6	74	27	14°	25228	25225	
SL-3MNF	9,5	6	74	27	14°			29070
SL-3ML6	9,5	6	177	27	14°	26778	26775	
SL-4M	12,7	6	76	28	14°	25253	25250	
SL-4MNF	12,7	6	76	28	14°			29072
SL-4ML6	12,7	6	178	28	14°	26803	26800	
* SL-5M	16	6	77	30	14°	25278	25275	
* SL-5MNF	16	6	77	30	14°			29074
* SL-7M	19	6	85	38	14°	25353	25350	
* SL-7MNF	19	6	85	38	14°			29078
SL-7MNF	19	8	85	38	14°			29080

